# Technical Data Sheet

## The Conservation Rooflight®

## Product Description

The Conservation Rooflight® is the original low profile skylight, combining the highest modern performance standards with an authentic traditional appearance. Favoured by English Heritage, the National Trust and Planning / Conservation Officers, it is available in a wide range of sizes, along with a Bespoke Design Service.

## Manufactured From

3mm mild steel with a protective polyester powder coating to BS EN ISO 12944.

The standard frame is finished in a textured semi gloss paint finish in black RAL 9005 (other RAL colour options are available).

All Conservation Rooflights® have internal linings which are pre-treated and sealed with a white coating (to a 10% gloss level).

COASTAL: Please note, for properties that reside within 5km of the coastline or large estuary, we recommend calling our Customer Services Team on 01993 833155 to discuss an appropriate alternative of stainless steel or steel treated with a hot Zinc Spray coating.

## Testing

CE
EN 14351-1: 2006+A1 : 2010

The Conservation Rooflight® range is CE marked in accordance with EN14351-1:2006+A1:2010.

Part L compliant and tested for water tightness to EN 1027:2000 - met class E1050.

The Conservation Rooflight® meets the requirements of BS6375-1:2009 exposure category 2000.



## Standard Glazing

4mm SGG Planilux Toughened Outer

16mm 90% Argon Cavity

4mm SGG Planitherm Total + (Low E) Toughened Inner

Whole unit u-value (Uw) of 1.5 W/m$^2$K in accordance with EN ISO 10077-2:2012.

Other glazing specifications are available upon request, contact us for more information.

## Sizes and Prices (for an 'on the rafter' installation)

| | | |
|---|---|---|
| **CR06-1** | (W) 412mm x (L) 520mm - | **£508** |
| **CR07-2** | (W) 463mm x (L) 622mm - | **£524** |
| **CR01-2** | (W) 565mm x (L) 725mm - | **£510** |
| **CR03-2** | (W) 565mm x (L) 1028mm - | **£574** |
| **CR08-2** | (W) 615mm x (L) 875mm - | **£623** |
| **CR09-2** | (W) 717mm x (L) 1028mm - | **£679** |
| **CR10-2** | (W) 717mm x (L) 1180mm - | **£733** |
| **CR14-2** | (W) 717mm x (L) 1333mm - | **£751** |
| **CR15-2** | (W) 717mm x (L) 1635mm - | **£877** |
| **CR01-3** | (W) 1021mm x (L) 725mm - | **£678** |
| **CR11-3** | (W) 869mm x (L) 1028mm - | **£755** |
| **CR13-3** | (W) 1021mm x (L) 1180mm - | **£835** |
| **CR14-3** | (W) 1021mm x (L) 1333mm - | **£877** |
| **CR15-3** | (W) 1021mm x (L) 1635mm - | **£1061** |
| **E1LG** | (W) 888mm x (L) 1114mm - | **£877** |
| **E1RG** | (W) 888mm x (L) 1114mm - | **£877** |

**Prices exclude accessories, VAT and delivery.**
**Sizes above are for an 'on the rafter' installation.**
**Please consult with us for 'between the rafter' sizes.**

**All prices are correct at the time of going to press.**

## Pitch

Suitable for pitched roof installations with a 17.5-65° roof pitch.

## Opening Options

**Manual hand winders**
Available in brass or chrome with opening distances of either 150mm or 300mm.

**Manual pole winder**
And winding crank for out of reach opening. Available in brass or chrome with opening distances of 150mm or 300mm. Poles are available in varying lengths from 1m to 3m.

**Motors**
Motorised opening options are available for out of reach rooflights and can be controlled by a switch or remote. Contact us for more information

**Fixed Shut**
A fixing bracket for a fixed shut roof window. The fixing bracket is white as standard.

## Optional Extras and Blinds

Roller blinds available in 71 colours.

Pleated blinds available in 14 colours.

Rain sensors, temperature sensors and other accessories are available on request. Please consult with us directly for compatibility.

## Flashing Kits

The Flashing Kit can be used for 'on the rafter' installations only, where the roof depth (above the rafter) does not exceed 75mm. This will result in the roof window sitting proud of the roof tiles.

For more information see Flashing Kit in Sizes Options and Prices.

For 'between the rafter' a (flush finish) installation it is recommended that Code 4 Lead is used.

## Lead Time

The Conservation Rooflight®. Subject to availability. The usual lead time is 5 working days for standards. Egress roof windows are 14 days. Please call if you require sooner.

## Installation

The Conservation Rooflight® Installation Manual and Installation Drawings are available to download from our website.

BIM Objects can also be downloaded.

## Warranty

Our steel rooflights and roof windows are guaranteed for 12 months in accordance with our Terms and Conditions.

Upon product registration with us, this guarantee can be extended as set out in our terms and conditions, provided that the appropriate products have been installed to suit their location and that these are regularly maintained, with these actions recorded in accordance with our maintenance instructions.



Visit **www.therooflightcompany.co.uk** or call us today on **01993 833108** for more information.

the Rooflight Company

July 2019-V3