HVP Security Shutters
Roller Shutter Manufacture and Installation

Chainlink Roller Grilles (CL200 / CL250)



Contemporary security roller grilles - lightweight and effective

Chainlink roller grilles combine modern and elegant lines with a large amount of open space. They are versatile security shutters, suitable for a range of different applications.

Manufactured from aluminium or steel tubes and links, put together with steel rods, chainlink grilles make a lightweight, but strong curtain. They are available in brick bond (CL200) and inline (CL250) patterns. A large area of open space between the links creates a sense of openness that makes Chainlink grilles a popular choice for shopfronts as well as reception counters, bars and serveries.

Key features

- Good visibility
- Effective security
- Contemporary design

Suitable for

- Retail shopfronts
- Reception areas
- Food serveries
- Counters and bars







AMENDMENT
ADUR & WORTHING
PLANNING SERVICES
PLAN | AWDM/ 0372/17
DATE VALID | Rec'd 15/2/17

Technical specification

CL200 - Brick bond
22mmW x 6mmH

CL250 - Inline
110mmW x 6mmH

Chainlink CL200/CL250 Roller Grille

Construction:
Manufactured from aluminium tubes and links on aluminium rods.
Tube size 111mm x 13mm; Link size 88mm x 16mm x 3mm;
Steel guides 65mm x 32mm or 50mm x 32mm;
Aluminium T-section Bottom rail.

Available in two patterns:
CL200 - brick bond pattern,
CL250 - inline pattern

Canopy:
Roll formed aluminium in two sections; top and bottom boxes. Bottom box removable for installation and maintenance.

Box size:
Clear opening height (to underside of box):

2400mm, box size 305mm
3000mm, box size 353mm
5000mm, box size 383mm

Operation:
Manual push up/pull down operation or electric operation by internal tubular motor with manual override facility. Safety brake fitted when required to comply with BS EN 1224-1:2003-1 (HVP Security Shutters' general policy is to fit a safety brake unless specified otherwise).

Locking Options:
Bottom rail central key lock, guide pin locks, or ground padlocking system. Electrically operated grilles are generally self-locking. For additional security HVP Security Shutters recommends guide pin locks or a ground padlocking unit combined with a motor isolator box.

Finish:
Anodised natural aluminium as standard. Also available in polished aluminium, stainless steel or powder coated.

Maximum Sizes:
CL200: 5000mmW x 5000mmH
CL250: 7000mmW x 5000mmH

Tube and link security roller grille with a high degree of visibility.

Unless noted otherwise, all drawings are for illustrative purposes only. Technical specifications are subject to change without notice. Please contact HVP Security Shutters for the latest information.