



08008 886633

07584 624744

[BACK TO PRODUCTS](#)

OUR PRODUCTS

Developer Range



Medium



Dark



Red



Brown



Rothschild Blend



Buff

We use cookies to ensure that we give you the best experience on our website. If you continue to use this site we will assume that you are happy with it.

[Ok](#)



08008 886633
07584 624744

blend's in sensitively with its surroundings.

The splendour of clay is that it has a beauty that will elegantly weather and mature slowly with age.

Technical

All our roof tiles are tested with our in house laboratory facility to meet current British standards – BS EN 538 Flexural strength, BS EN 539-1 Impermeability & BS EN 539-2 Frost resistance, we then further test them independently with Ceram, a global expert in material testing and analysis, approved by both UKAS and the British standards institute.

Tile Fixing

Traditional Clay Roof Tiles must be laid and fixed to comply with BS 5534: the British Standard Code of practice for slating and tiling, and BS 8000: Part 6: the British Standard Code of practice for workmanship on building sites. The code of practice for tiling and slating also recommends clay tiles should be mixed from three pallets when being loaded out.

*We guarantee our products to a minimum roof pitch of 35 degrees. The British Standard Code of practice for slating and tiling recommends a minimum roof pitch of 40 degrees for handmade tiles.

On site Safety: Pallets should be offloaded onto firm level ground.

Technical Data	Roof	Vertical
Minimum roof pitch	35°	90°
Headlap (minimum)	65 mm	38 mm

We use cookies to ensure that we give you the best experience on our website. If you continue to use this site we will assume that you are happy with it.



08008 886633
07584 624744

Covering capacity	60.0 tiles per m ²	53.0 tiles per m ²
Cover width	165 mm	165 mm
Weight as laid	72.0 kg per m ²	63.6 kg per m ²
Weight per 1000	1.2 tonnes	1.2 tonnes
Weight per tile	1.2 kg	1.2 kg
Battens per m ²	10 m	8.8 m
Batten size – up to 450 mm after centres	38 x 25 mm	38 x 25 mm
Batten size – up to 600 mm after centres	38 x 25 mm	38 x 25 mm
Nail size/type for tiles	38 x 3.35 mm aluminium ring shank clout head	38 x 3.35 mm aluminium ring shank clout head

	Nominal size (mm)	Pack Quantity	“Unit Weight (average) kg”	“Pack Weight kg”
Plain Tile	265 x 165	1000	1.25	1250

We use cookies to ensure that we give you the best experience on our website. If you continue to use this site we will assume that you are happy with it.



08008 886633

07584 624744

--	--	--	--	--

**TRADITIONAL****PRIVACY****COOKIES****LINKS****FAQ****DOWNLOADS**

Company Reg. No. 08281620. VAT No. 150 8505 26.

We use cookies to ensure that we give you the best experience on our website. If you continue to use this site we will assume that you are happy with it.