REVISED **Window: Specification**

SPECIFICATION:

Compliant with Document 'L' (Part 'L') of Building Regulations

- (White) 100% Virgin PVCu - to **prevent discolouration,** welded corners, approx 3mm outer wall - for strength and to prevent warping and cracking, **NEW 5 chambered profiles** also for strength


- **NEW 28mm Double glazed units,** manufactured to **Bs5713** and new **EN1279-2.** Fabricated **including Pilkington 'K'** Low Emissivity (Low 'E') glass for greater thermal efficiency and to comply with Document 'L'- Low Emissivity glass allows heat from the sun into your home but reflects from internal sources, such as radiators, back into your house.

- White push-to-open, **key locking** handles

- **Multi-point,** mushroom head, espagnolette **locks** with night vent facility (window can be locked when slightly open for ventilation)

- **NEW Internally beaded,** fully welded system for **strength and security** - designed to prevent the external removal of the double glazed sealed unit by a potential intruder

Positively locating, stainless steel friction stays (hinges)



Colour: **white**, Style: **W6**, Sizes: **1150 x 1000**, Cill: **no cill**, Window Board: **no_board**, Handles: **white**, Shootbolt Locking: **no**, Trickle Vents: **1**, Glass Decoration: **no**, Obscure Glass: **yes**, Toughened Glass: **no**, Fixing Pack: **no**