USER INSTRUCTIONS

TECHNICAL DATA

Item \ Model / Datasheet		VEC01	VEC02	VEC03	VEC04
Input	Power Supply	1P+N+PE	3P+N+PE	1P+N+PE	3P+N+PE
	Rated Voltage	AC220 ~ 240V 50/60Hz	AC380 ~ 450V 50/60Hz	AC220 ~ 240V 50/60Hz	AC380 ~ 450V 50/60Hz
	Rated current	Max 32A (6-32A adjustable)			
Output	Output Voltage	AC220 ~ 240V 50/60Hz	AC380 ~ 450V 50/60Hz	AC220 ~ 240V 50/60Hz	AC380 ~ 450V 50/60Hz
	Maximum Current	Max 32A (6-32A adjustable)			
	Rated Power	7.4KW	22KW	7.4KW	22KW
User interface	Charger socket or connector	Type 2			
	Material	ABS +PC Flammability Rating V - 0			
	Colour	Black			
	Indicator light	Three colour LED			
Safety	Ingress Protection	IP54		Enclosure: IP65 Connector:IP54	
	PCB protection	Over current protection The max 32A-Recommended 36A			
		Residual current protection (AC 30mA Type A, DC6mA)			
		Earth check			
		Over/Under voltage protection			
		Over temperature			
		PEN fault protection			
	Certification	CE, UKCA			
	Certification Standard	EN 61851,EN 62196			
Power consumption	Standby power consumption	<10W			
Enviroment	Installation	Wall mounted			
	Work Temperature	-25˚C~50˚C			
	Work Humidity	3%~95%			
	Work Altitude	<2000m			

For Customer Services & Spare Parts please call 0161 249 6780
Opening times: Monday - Friday 8am – 5pm