DO NOT SCALE FROM THIS DRAWING

THE CONTRACTOR SHOULD VERIFY ALL DIMENSIONS BY SITE MEASUREMENT PRIOR TO ORDERING MATERIALS OR MANUFACTURING COMPONENTS

READ THIS DRAWING IN CONJUNCTION WITH ALL STRUCTURAL ENGINEERS + ARCHITECTS INFORMATION

REPORT ANY DISCREPANCIES TO THE ARCHITECT IMMEDIATELY & AWAIT DIRECTION

EXISTING SLATE ROOF + FELT RETAINED IN SITU + OVERLAID WITH NEW SLATES ON BATTENS AS DETAIL

CONTINUOUS FELT GUTTER FORMED IN TRAPEZOIDAL SECTION

NOTCH OBTUSE INSULATED TRIANGULAR BATTEN OVER RAFTERS + ALL JOINTS TAPED

KNAUF TRIAXIAL LAMINATE REINFORCED DATA VAPOUR RETARDER APPLIED TO FACE OF RAFTERS WITH MASTIC SEAL AT EDGES & SKIMMED OVER TO FORM CONTINUOUS VAPOUR BARRIER

PAINTED SOFFIT WITH RECESSED DOWNLIGHTS TO SUIT. NOTE OF SPECIALIST

EXISTING PURLIN RETAINED + NEW CONCEALED STEEL TO SUPPORT EXISTING

EAVES SOFFIT LINED OUT IN PLASTIC BOARD

FLASHING CONCEALED WITH LEADWORK

EAVES DETAIL UNCHANGED, CONTINUOUS INSULATION ABOVE TO BE PROVIDED

NEW SOLID FLOOR JOISTS TO STRUCTURAL ENGINEERS SPECIFICATION BELOW EXISTING FLOOR LEVEL

EXISTING TIMBER JOISTS TO REMAIN UNDISTURBED

NEW SOLID FLOOR JOISTS CUT TO FORM STEPPED OPENING TO SUIT ENGINEERS DETAIL

NEW TIMBER TO MATCH EXISTING TO BE PAINTED

NEW CONCRETE HEARTH & SUPPORT ON NEW CONCRETE FLOOR

EXISTING TIMBER JOISTS TO REMAIN UNDISTURBED

NEW TIMBER JOISTS CUT TO FORM STEPPED OPENING TO MATCH EXISTING

NEW CONCRETE HEARTH & SUPPORT ON NEW CONCRETE FLOOR

EXISTING TIMBER JOISTS TO REMAIN UNDISTURBED

NEW TIMBER JOISTS CUT TO FORM STEPPED OPENING TO MATCH EXISTING

NEW CONCRETE + STAIRS IN PAINTED FINISH TO SECOND FLOOR AT 42°

TIMBERS ENCASE THE INFILL WITH FLUSH CONCEALED DOOR.

LINE OF PLASTER TO UNDERSIDE OF SOFFIT UNDER GABLES SHOWN DOTTED & COMPLETED WITH MASTIC TO ENSURE AIR TIGHT CONTINUOUS RETAINING FACE

EXISTING SLATE ROOF + FELT RETAINED IN SITU + OVERLAID WITH NEW SLATES ON BATTENS AS DETAIL

CONTINUOUS FELT GUTTER FORMED IN TRAPEZOIDAL SECTION

NOTCH OBTUSE INSULATED TRIANGULAR BATTEN OVER RAFTERS + ALL JOINTS TAPED

KNAUF TRIAXIAL LAMINATE REINFORCED DATA VAPOUR RETARDER APPLIED TO FACE OF RAFTERS WITH MASTIC SEAL AT EDGES & SKIMMED OVER TO FORM CONTINUOUS VAPOUR BARRIER

PAINTED SOFFIT WITH RECESSED DOWNLIGHTS TO SUIT. NOTE OF SPECIALIST

EXISTING PURLIN RETAINED + NEW CONCEALED STEEL TO SUPPORT EXISTING

EAVES SOFFIT LINED OUT IN PLASTIC BOARD

FLASHING CONCEALED WITH LEADWORK

EAVES DETAIL UNCHANGED, CONTINUOUS INSULATION ABOVE TO BE PROVIDED

EXISTING TIMBER JOISTS TO REMAIN UNDISTURBED

NEW TIMBER JOISTS CUT TO FORM STEPPED OPENING TO MATCH EXISTING

NEW CONCRETE HEARTH & SUPPORT ON NEW CONCRETE FLOOR

EXISTING TIMBER JOISTS TO REMAIN UNDISTURBED

NEW TIMBER JOISTS CUT TO FORM STEPPED OPENING TO MATCH EXISTING

NEW CONCRETE + STAIRS IN PAINTED FINISH TO SECOND FLOOR AT 42°

TIMBERS ENCASE THE INFILL WITH FLUSH CONCEALED DOOR.

LINE OF PLASTER TO UNDERSIDE OF SOFFIT UNDER GABLES SHOWN DOTTED & COMPLETED WITH MASTIC TO ENSURE AIR TIGHT CONTINUOUS RETAINING FACE