

Design Settings

Rainfall Methodology	FEH-22	Minimum Velocity (m/s)	1.00
Return Period (years)	100	Connection Type	Level Soffits
Additional Flow (%)	10	Minimum Backdrop Height (m)	0.200
CV	1.000	Preferred Cover Depth (m)	1.200
Time of Entry (mins)	5.00	Include Intermediate Ground	✓
Maximum Time of Concentration (mins)	30.00	Enforce best practice design rules	✓
Maximum Rainfall (mm/hr)	50.0		

Nodes

Name	Area (ha)	T of E (mins)	Cover Level (m)	Easting (m)	Northing (m)	Depth (m)
Type A	0.008	5.00	13.000	17.233	60.999	3.000

Simulation Settings

Rainfall Methodology	FEH-22	Analysis Speed	Detailed	Starting Level (m)	
Rainfall Events	Singular	Skip Steady State	x	Check Discharge Rate(s)	x
Summer CV	1.000	Drain Down Time (mins)	1440	Check Discharge Volume	x
Winter CV	1.000	Additional Storage (m³/ha)	0.0		

Storm Durations

15 | 30 | 60 | 120 | 180 | 240 | 360 | 480 | 600 | 720 | 960 | 1440 | 2160

Return Period (years)	Climate Change (CC %)	Additional Area (A %)	Additional Flow (Q %)
2	0	0	0
10	0	0	0
30	40	10	0
100	45	10	0

Node Type A Soakaway Storage Structure

Base Inf Coefficient (m/hr)	0.00000	Invert Level (m)	10.000	Depth (m)	2.000
Side Inf Coefficient (m/hr)	0.02412	Time to half empty (mins)	2836	Inf Depth (m)	2.000
Safety Factor	2.0	Pit Width (m)	2.000	Number Required	1
Porosity	0.95	Pit Length (m)	3.000		

Results for 2 year Critical Storm Duration. Lowest mass balance: 100.00%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m ³)	Flood (m ³)	Status
1440 minute winter	Type A	960	10.408	0.408	0.1	2.3232	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	Outflow (l/s)
1440 minute winter	Type A	Infiltration	0.0

Results for 10 year Critical Storm Duration. Lowest mass balance: 100.00%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
600 minute winter	Type A	555	10.723	0.723	0.3	4.1205	0.0000	OK
Link Event (Upstream Depth)	US Node	Link	Outflow (l/s)					
600 minute winter	Type A	Infiltration	0.0					

Results for 30 year +40% CC +10% A Critical Storm Duration. Lowest mass balance: 100.00%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
960 minute summer	Type A	945	11.399	1.399	0.6	7.9766	0.0000	OK

Link Event (Upstream Depth)	US Node	Link	Outflow (l/s)
960 minute summer	Type A	Infiltration	0.0

Results for 100 year +45% CC +10% A Critical Storm Duration. Lowest mass balance: 100.00%

Node Event	US Node	Peak (mins)	Level (m)	Depth (m)	Inflow (l/s)	Node Vol (m³)	Flood (m³)	Status
1440 minute summer	Type A	1320	11.789	1.789	0.5	10.1982	0.0000	OK
Link Event (Upstream Depth)	US Node	Link	Outflow (l/s)					
1440 minute summer	Type A	Infiltration	0.1					